

Pandromeda

Fractional Brownian Motion (fBm)

What is it?

- Generalization of *Brownian motion*:
Integral of progress on a random walk
- fBm is characterized by its *power spectrum*
Brownian motion has $1/f^2$ power spectrum
fBm has $1/f^b$ power spectrum, $1.0 = b = 3.0$
- Just think of b as controlling roughness of the terrain
- For math, see Voss & Saupe in "The Science of Fractal Images"

Ken "Doc Mojo" Musgrave SIGGRAPH 2001

Pandromeda

Fractional Brownian Motion (fBm)

The key variables

- Basis function:
The shape that is repeated over a range of scales
- Spectral exponent:
Determines fractal dimension, or roughness of terrain
- Lacunarity:
The gap between successive scales
- Octaves:
The number of scales of self similarity

Ken "Doc Mojo" Musgrave SIGGRAPH 2001

Pandromeda

Fractional Brownian Motion (fBm)

The basis function

- Should have range $[-1.0 \dots 1.0]$
So that integral remains zero
Expected value remains zero
- Shape is very important
Shape clearly shows through in fractal sum
(At lacunarity of 2.0)
- Can be literally anything!
Sparse convolution (wavelets) gives maximum flexibility
But is very expensive
(See Peachey in "Textures and Modelling: A Procedural Approach")

Ken "Doc Mojo" Musgrave SIGGRAPH 2001

Pandromeda

Fractional Brownian Motion (fBm)

The basis function

- Sine wave in Fourier synthesis
Mathematically pure: each frequency is defined exactly
Sine is periodic, so all finite sums of it are also periodic
- Triangle wave in polygon subdivision
Piecewise linear interpolation
Creases and sharp peaks
- Perlin noise
Piecewise cubic interpolation
Nice, aperiodic sine-wave substitute
- Others
Voronoi (see Worley, SIGGRAPH 96)
See list of basis functions in MojoWorld in CAL

Ken "Doc Mojo" Musgrave SIGGRAPH 2001

Pandromeda

Fractional Brownian Motion (fBm)

The basis function

- Batch algorithms
Fourier synthesis
Polygon subdivision
- Point-evaluated
Perlin noise, Voronoi, sparse convolution
These are the so-called "procedural" methods
- Infinite support
Sine waves
Procedural noises
- Finite support
Polygon subdivision
Wavelets

Ken "Doc Mojo" Musgrave SIGGRAPH 2001


Pandromeda

Fractional Brownian Motion (fBm)

The spectral exponent

- Determines the fractal dimension
- Or the roughness of our terrain
- Can be used correctly or incorrectly
- But you get a fractal nonetheless
See the course notes for the math
And the literature for unexpected complications
- But don't worry—use it qualitatively and ignore the math!

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Fractional Brownian Motion (fBm)

Lacunarity

- The gap between frequencies in spectral summation
- Virtually always set to 2.0 (hence "octaves")
- May want to use 2.0 ± 0.1
 - To avoid artifacts in lattice-based noises
 - As with value & gradient Perlin noises
- Using values $\ll 2.0$
 - Slower: takes more octaves to get fine details
 - Gains little, visually
- Using values $\gg 2.0$
 - Faster: takes less octaves to get fine details
 - But discrete frequencies can show through

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Fractional Brownian Motion (fBm)

Octaves

- Number of octaves is number of scales of self similarity
- Octaves are only "octaves" when lacunarity is 2.0
- Octaves = detail
- Can be driven by Nyquist limit
 - To antialias by *clamping*
 - As in QAEB tracing (see "Textures and Modelling")
 - Yields pixel-sized detail everywhere

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Fractal Terrain Models

Different kinds

- **Fourier:**
 - The most mathematically "pure"
 - Slow and periodic
- **Polygon subdivision:**
 - Easiest to implement, but sports the worst artifacts
 - Triangle, square, nested, unnested, semi-nested
 - (see Miller, SIGGRAPH 86, and "The Science of Fractal Images")
- **Point-evaluated / procedural:**
 - Can be the slowest, depending on basis function
 - Most flexible and, generally, best-looking

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Fractal Terrain Models

Point-evaluated or procedural

- Perlin noise fBm
 - Generalization of Perlin's "chaos" function
 - (See Perlin, *An Image Synthesizer*, SIGGRAPH 85)
- General procedural fBm
 - Same as above
 - But using Voronoi noise, sparse convolution, etc.
- Domain-distorted procedural fBm
 - Add a vector-valued function to the point, before evaluation
 - Shmushes the resulting fractal around

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Fractal Terrain Models

Point-evaluated or procedural

The basic algorithm:

1. Start with lowest frequency (largest scale of basis)
2. Double the frequency
3. Scale amplitude down, according to spectral exponent
4. Add in new, scaled frequency
5. Goto 2.

Ken "Doc Mojo" Musgrave SIGGRAPH 2001



Code for Procedural fBm

```


fBm( Vector point,
      NoiseFunction basis(),
      real exponent, real lacunarity,
      integer octaves )
{
    real value = 0.0, amplitude = 1.0;

    for ( i=0; i<octaves; i++ ) {
        value += basis(point) * amplitude;
        point *= lacunarity;
        amplitude *= exponent;
    }

    return value;
}

```

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Multifractals

Heterogeneous terrain models

- fBm is *stationary*: statistically homogeneous and isotropic
- Real terrain is far more complex
 - Mountains rise from plains
 - Peaks and valleys have different roughnesses, etc.
- We want to capture at least some of this
 - Devising heterogeneous fBm-based fractals
 - While preserving the elegance of fBm

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Multifractals

Three multifractal terrain models

- Stats-by-altitude
 - Conjecture: valleys are smoother than peaks
 - Model: multiply each octave (after first) by current "altitude"
- "Pure" multiplicative multifractal
 - Inner loop is multiplicative, rather than additive as in fBm
 - Problem: converges to zero or diverges to infinity
- Hybrid additive/multiplicative multifractal
 - Conjecture: valleys should be smoother at all altitudes
 - Model: multiply octave i by value of octave $i-1$; sum this

Ken "Doc Mojo" Musgrave SIGGRAPH 2001



Code for Stats-by-Altitude Multifractal


```
StatsByAlt( Vector point, NoiseFunction basis(),
  real exponent, real lacunarity,
  integer octaves )
{
  real value, amplitude = 1.0;

  if ( octaves ) // do first octave
    value = basis( point );

  for ( i=1; i<octaves; i++ ) {
    value += value * basis(point) * amplitude;
    point *= lacunarity;
    amplitude *= exponent;
  }

  return value;
}
```

Ken "Doc Mojo" Musgrave SIGGRAPH 2001




Code for Multiplicative Multifractal

```
Multifractal( Vector point,
  NoiseFunction basis(),
  real exponent, real lacunarity,
  integer octaves )
{
  real value = 1.0, amplitude = 1.0;

  for ( i=0; i<octaves; i++ ) {
    value *= basis(point) * amplitude;
    point *= lacunarity;
    amplitude *= exponent;
  }

  return value;
}
```

Ken "Doc Mojo" Musgrave SIGGRAPH 2001



Code for Hybrid Multifractal

```
HybridMF( Vector point, NoiseFunction basis(),
  real exponent, real lacunarity,
  integer octaves )
{
  real value, signal, weight, amplitude = 1.0;


  if ( octaves <= 0 ) return 0.0;

  weight = value = basis( point ); // first octave
  octaves -= 1.0;

  for ( i=1; i<octaves; i++ ) {
    signal = weight * basis(point) * amplitude;
    value += signal;
    weight = signal;
    point *= lacunarity;
    amplitude *= exponent;
  }

  return value;
}
```

Ken "Doc Mojo" Musgrave SIGGRAPH 2001



Erosion

- Erosion is what shapes terrains
 - Bedrock is fractal; erosion works on this fractal substrate
 - Creates *context-sensitive* fractals: river networks
- Diffusive erosion
 - Dry creep, rain splash, animal activity, etc.
 - Equivalent to low-pass filter—can operate very efficiently
- Fluvial erosion: running water
 - Rivers and glaciers are principal geomorphic agents
 - Very important—but too hard to implement and slow to run!
 - (see Musgrave et al, SIGGRAPH 89, and geology literature)

Ken "Doc Mojo" Musgrave SIGGRAPH 2001

Pandromeda

Conclusions

- Fractal models capture complexity, with simplicity
- *Amplification*: wealth of detail from simple model
- Height field terrain models don't cut it
- fBm doesn't cut it
- Multifractal models are a little better
- Dilation symmetry rocks!
- Alas, Nature is more complex than fractal geometry

Ken "Doc" Major, Musgrave SIGGRAPH 2001